



REP 06 LR REP 11 LR

TUCKAWAY TAIL-LIFTS

LOAD CAPACITY: 600, 1150 KG
1320, 2500 LB



DESCRIPTION

The REP folding tail-lifts are the ideal tail-lifts for distribution, vehicle rental companies, for vehicles where the maximum variable use is needed and/or vehicles for docking work.

REP 06 LR is very light and compact. Therefore, it is suitable for small vehicles from 3.5 to 7 tons.

REP 11 LR for vehicles weighing 7 tons or more.

SPECIFICATIONS

Platform depth:	from 950 to 1550 mm
Platform width:	2000 mm max
Lift cylinders:	1
Tilt cylinders:	none
Autotilt at ground:	none - level ride
Platform opening:	Manual opening
Power supply:	12 or 24 V
Frame color:	Black KTL plus and powder paint
Weight:	from 211 Kg

SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Blinking lights on platform;
- Roll stop;
- Light brackets





REP 06 LR REP 11 LR

TUCKAWAY TAIL-LIFTS

LOAD CAPACITY: 600, 1150 KG
1320, 2500 LB

TECHNICAL DATA

Mod.	Load capacity (centre to centre at 600 mm - 23 in)	Standard platform dimensions Deep x Width	Weight *	Floor to ground (max)	Mounting space (min)
REP 06 LR C	600 Kg 1320 lb	950 x 1500 mm / 37 x 59 in	211 Kg / 465 lb	990 mm 39 in	935 mm 36,8 in
		1050 x 1500 mm / 41 x 59 in	216 Kg / 476 lb		
		1150 x 1500 mm / 45 x 59 in	221 Kg / 487 lb		
REP 06 LR H	600 Kg 1320 lb	950 x 1500 mm / 37 x 59 in	222 Kg / 489 lb	1130 mm 44,5 in	1028 mm 40,5 in
		1050 x 1500 mm / 41 x 59 in	227 Kg / 500 lb		
		1150 x 1500 mm / 45 x 59 in	232 Kg / 511 lb		
		1250 x 1500 mm / 49 x 59 in	237 Kg / 522 lb		
REP 11 LR H	1150 Kg 2500 lb	950 x 2000 mm / 37 x 78 in	235 Kg / 518 lb	1130 mm 44,5 in	1118 mm 44 in
		1050 x 2000 mm / 41 x 78 in	240 Kg / 529 lb		
		1150 x 2000 mm / 45 x 78 in	245 Kg / 540 lb		
		1250 x 2000 mm / 49 x 78 in	250 Kg / 551 lb		
REP 11 LR HS	1150 Kg 2500 lb	1050 x 2000 mm / 41 x 78 in	245 Kg / 540 lb	1250 mm 49,2 in	1165 mm 45,9 in
		1150 x 2000 mm / 45 x 78 in	250 Kg / 551 lb		
		1250 x 2000 mm / 49 x 78 in	255 Kg / 562 lb		
		1450 x 2000 mm / 57 x 78 in	265 Kg / 584 lb		
REP 11 LR HSS	1150 Kg 2500 lb	1150 x 2000 mm / 45 x 78 in	257Kg / 566 lb	1420 mm 55,9 in	1317 mm 51,8 in
		1250 x 2000 mm / 49 x 78 in	262 Kg / 577 lb		
		1450 x 2000 mm / 57 x 78 in	272 Kg / 599 lb		
		1550 x 2000 mm / 61 x 78 in	274 Kg / 604 lb		

*Weight does not include rear cross member (30 Kg - 66 lbs). The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.



LOW MAINTENANCE BUSHES AND CHROMIUM PLATED PINS.



POWDER COATING PAINT (2) ADDED TO KTL PLUS (1). NO RUST AND NO SALT STAINS.



HI-TENSILE ALUMINUM SPECIALISTS SINCE 1992.



LOW NOISE POWER UNIT & NO ELECTRONICS = EASY MAINTENANCE

01/2021