



**F3 RE 10 AM**  
**F3 RE 17 AM**  
**F3 RE 22 AM**

**RETRACTABLE TAIL-LIFT**  
**WITH ALUMINIUM GUIDES**

LOAD CAPACITY: 1000, 1700, 2200 KG



**DESCRIPTION**

F3 RE 10/17/22 AM with Aluminium Sldyers, so attractive pricing and ideal to equip rental vehicles.

The 5 cylinders F3 RE 10/17/22 AM is a strong and compact lift, with very high performances. Smooth hydraulic automatic tilt, high stiffness ideal to equip vehicles for customers that like high performances.

The F3 RE 10 is available with a wide variety of versions, with single or double fold platforms, to suit commercial trucks up to 12 T GVW.

**The F3 RE 17/22 AM is available with double fold platforms only and can fit on rigid, trailers or semi-trailers form 10 T GVW and up. (for single fold platform version please refer to F4 RE 17/22).**

**SPECIFICATIONS**

Platform:	Aluminium
Platform depth:	from 1283 to 1783 mm rear bumper EEC type approved
Lift cylinders:	2
Tilt cylinders:	2
Autotilt at ground:	hydraulic (with memory feature)
Sliding system:	Alloy guides and hydraulic motor
Power supply:	12 or 24 V
Low maint. bushes:	greasable
Frame color:	Black KTL plus and powder paint
Weight:	from 395 Kg

**SUGGESTED OPTIONS**

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Blinking lights on platform;
- Roll stop;
- Torsion bar





**F3 RE 10 AM**  
**F3 RE 17 AM**  
**F3 RE 22 AM**

**RETRACTABLE TAIL-LIFT**  
**WITH ALUMINIUM GUIDES**

LOAD CAPACITY: 1000, 1700, 2200 KG

**TECHNICAL DATA**

	Mod.	Load capacity (centre of gravity at 600 mm)	Floor to ground (max)	Platform Depth* (example)	Mounting space (min)	Weight* Kg
Single fold platform	F3 RE 10 C AM	1000 Kg	1070	1560 (600+960)	1473	430
	F3 RE 10 H AM		1225	1660 (600+1060)	1630	455
	F3 RE 10 HS AM		1450	1755 (750+1005)	1878	480
Double fold platform	F3 RE 10 H AM	1000 Kg	1225	1305 (700+605)	1092	395
	F3 RE 10 HS AM		1450	1600 (850+750)	1245	460
	F3 RE17 H AM	1700 Kg	1290	1283 (700+583)	1232	485
	F3 RE 17 HS AM		1530	1583 (850+733)	1383	520
	F3 RE 17 HSS AM		1670	1783 (950+833)	1490	560
	F3 RE 22 H AM	2200 Kg	1290	1283 (700+583)	1232	505
	F3 RE 22 HS AM		1530	1583 (850+733)	1383	545
	F3 RE 22 HSS AM		1670	1783 (950+833)	1490	585

01/2021

\*Approximate weight for tail-lift equipped with aluminium platform 2450 mm wide.


The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.



**LOW MAINTENANCE BUSHES AND CHROMIUM PLATED PINS.**



**POWDER COATING PAINT (2) ADDED TO KTL PLUS (1). NO RUST AND NO SALT STAINS.**



**HI-TENSILE ALUMINIUM SPECIALISTS SINCE 1992.**



**LOW NOISE POWER UNIT & NO ELECTRONICS = EASY MAINTENANCE**